



EIE INSTRUMENTS PVT. LTD.
(An ISO 9001:2015 Certified Company)

TENSILE TESTING MACHINE-DIGITAL-25 KN-SERVO CONTROLLED SYSTEM



Compliance Standards:

ASTM D882, ASTM D828, ASTM D1938, ASTM D1876, ASTM D638, ASTM F88, ASTM F904, ASTM D2256, ASTM D5034, ASTM D412, ISO 1924, TAPPI T494

Grips Applications:

GRIPS can be supplied for one of the following applications at extra cost (Quoted as separate item). Please specify your application at the time of order. Please refer to the accessories quote.

Applications:

1. Flexible laminated and formed pouches **Or**
2. Paper and Paper Kraft **Or**
3. Yarn/Fabric/Rubber **Or**
4. Plastic and Polymer testing **Or**
5. Fine wire testing **Or**
6. G.I. Wire testing, Brass, Copper, Aluminum fine wire testing **Or**
7. Vulcanized rubber/Elastomer

Introduction:

Computerized Tensile testing machine capacity **0-2500 Kgf (25 KN) (25000 N)** with software program and built-in ball screw operated through precisely controlled **SERVO MOTOR & SERVO FEEDBACK LOOP SYSTEM with SERVO DRIVE** (for speed variation from **0.01mm/min to 500mm/min**) with encoder to measure the elongation. Also supplied with one pair of grip for any of the above

listed applications.

Salient Features

- Floor standing model
- Aesthetic outer appearance
- Unique and compact design features
- **Fitted with Highly précised combination of PLC & HMI System, Servo Motor and Drive System**
- Computer interfacing through RS-232 USB cable
- Equipped with Ball screw for friction less traverse
- Rotary encoder to obtain high accuracy in elongation measurement
- SERVO MOTOR & DRIVE for various combination of speed variation as per following
- **High Torque at very Low Speed**
- **High Torque at High Speed**
- Calibration of entire Machine at Very Low Speed
- Easy to use display unit and software
- On screen display of Maximum Load, Breaking Load, Yield Load, Elongation, and speed variations
- On screen Display of load v/s elongation (stress v/s strain) graph also get a excel sheet with a single click
- Supplied complete with PLC main unit, 7" colour touch HMI, Single Channel Load cell measurement module, PLC to HMI Communication cable and Dedicated SERVO Gear Box.

Protection

- Overload protection for load cell
- Over travel of traversing crosshead in both direction
- Automatic stopping and return of cross head at original position immediately on breakage/Failure of specimen
- Higher traverse speed
- Emergency Manual switch for stopping the machine

Software facility (Standard Supply)

- Specially designed Windows based Graphical Dedicated Software
- RS 232 interface with WINDOW based software to conduct the test directly from software itself
- Can store generated data with corresponding graph
- Can also store Yield Load, Yield Extension, Break Load, Break Extension, Max load and Modulus of Elasticity
- User can export the generated data in various file formats such as i.e. Excel, PDF etc
- Large Storage capacity (More than 50,000 tests) Depending upon Hard Disk capacity.
- User can change the design of generated graphs i.e. Line, Doted line, etc facility in graph
- Graph Grids color combination facility
- Graph zooming facility
- Individual graph comparison facility
- Graph overlapping facility for analysis of material property
- Auto scaling facility
- Company logo insertion facility
- Software can run various tests and can recall data for any test conducted the in history. (If Saved)
- Software is Menu Driven for easy navigation.
- Test reports and graphs directly printed on terminal printer through direct print commands
- Data and Result Units Selectable
- User can operate the machine directly from the software itself

Note:

- **Please specify the test application at the time of order for preparation of the Test Jaws (Grips) accordingly.**

- Jaw of the machine will be provided as per your application. Please clarify the same at the time of ordering. Offer for Jaws/Grips will be quoted as separate item.
- User can also utilize this machine for other than here listed ASTM Standards & test applications complying with suggested speed range and load capacity. Please call us for any clarifications.

Technical Specification

•Exterior Body Paint	:	Powder coated
•Display	:	Digital LCD Display
•Capacity	:	0 - 2500 Kgf (0-25000 N) (25 KN)
•Load cell	:	'S Type' load cell / Spherical Load Cell of reputed make
•Vertical daylight in mm	:	1000 mm
•Horizontal daylight in mm	:	400 mm
•Results displayed on screen	:	Load, Elongation values, Testing speed and type of test
•Least count for elongation	:	0.01 mm
•Least count for load	:	10 grams (0.01 kg)
•Speed Range	:	0.01 mm to 500mm/min
•Speed Variations	:	From 0.01mm/min to 500mm/min
•Load units	:	Kg, Newton & KN as per selection
•Motor for speed variations	:	SERVO Motor with dedicated SERVO Drive
•SERVO MOTOR make	:	Reputed make
•Speed control	:	Through Dedicated Servo Drive
•Servo Motor Rating	:	2 KW
•Transformer Ratings	:	1 KVA
•PLC Module	:	Reputed make
•HMI Module	:	Reputed make
•HMI Screen	:	7" Colour touch screen display
•Test jaws	:	Tensile jaws extra at actual as per ASTM D638/ASTM D882/ASTM D1876
•No. of screws	:	Dual screw mechanism driven through reputed make motor & gearbox
•Power Supply	:	440 Volt, 50 Hz, three Phase, AC Supply

Corporate Office:

A-1301, BVR Ek, Opp. Hotel Inder Residency,
Near Gujarat College, Ellisbridge,
Ahmedabad-380 006.
Phone : (079) 6621 1234
Website : www.eieinstruments.com

Calibration Laboratory:

Survey No. 1098, Nr. Mahakali Temple,
Opp. Primary School, Village Kubadthal,
Tal-Daskroi, Ahmedabad-382 433.
Phone: (079)-3520 8300
E-mail : info@eieinstruments.com

GST TIN No. : 24AABCE4018L1ZU
I.T. PAN No. : AABCE 4018L
IEC No. : 0813026598 Dt. 04/03/2014
CIN No. : U29199GJ2004PTC045078
TAN No. : AHME00572F