



EIE INSTRUMENTS PVT. LTD.
(An ISO 9001:2015 Certified Company)

CURING COMPOUND MOULD WITH ACCESSORIES



053.psd

Compliance standards

ASTM C156-03, IS 10080

Construction details :

- The mould is made of stainless steel material and it is water tight as per the standard requirement.
- The mould is rigidly constructed to prevent distortion and it is thoroughly cleaned.
- The interior faces of the mould are plane surface.
- The mould is measured as 150mm x 300mm at the top, 143 x 295 mm at bottom, and 50 mm deep on the inside surface.
- The mould is flat rim at the top on all sides approximately 6mm in width.
- **A wooden float with dimension of 75 mm x 280 mm x 20 mm thick will also be part of standard supply. The pocking rod to be supplied with the mould is made of non absorbent, non abrasive, non brittle rubber compound material.**
- **The pocking rod is 150mm long and has cross sectional dimensions of 25mm x 12 mm with tamping face in the form of a blunt torpedo.**

Corporate Office:

A-1301, BVR Ek, Opp. Hotel Inder Residency,
Near Gujarat College, Ellisbridge,
Ahmedabad-380 006.
Phone : (079) 6621 1234
Website : www.eieinstruments.com

Calibration Laboratory:

Survey No. 1098, Nr. Mahakali Temple,
Opp. Primary School, Village Kubadthal,
Tal-Daskroi, Ahmedabad-382 433.
Phone: (079)-3520 8300
E-mail : info@eieinstruments.com

GST TIN No. : 24AABCE4018L1ZU
I.T. PAN No. : AABCE 4018L
IEC No. : 0813026598 Dt. 04/03/2014
CIN No. : U29199GJ2004PTC045078
TAN No. : AHME00572F