



EIE INSTRUMENTS PVT. LTD.
(An ISO 9001:2015 Certified Company)

ULTRASONIC DRILLING MONITOR - RSM-HGT(D)



Application:

- Hole quality testing of bored piles on railway, highway, port, high-rise building and etc.
- Hole quality testing of branch and plate piles.
- Trenching quality testing of the groove of diaphragm wall.

Technical Characteristics:

- It supplies fast printing, the test results can be printed directly on situ. The whole testing process and probe lift system is automatically controlled.
- The minimum detectable bore diameter is 600mm while the maximum is 8000mm, and max mud weight can be 1.4.
- The device can be automatically corrected according to the pore size to ensure the test result is accurate and reliable.
- The device can real-time output image of two profiles, that is, XX' and YY' profile deviation curves and tables. (Including depth, sonic time of each measuring point, distance between probe and hole wall, pore diameter, offset value and verticality on the position of measuring point.)
- The analyzing software compatible with Windows XP/Win7/Win8/Win10 operating system
- Can be easily imported into Word and Excel for work reports.
- With a variety tables and report forms to meet the requirement of report.

Note:

EIE Instruments Pvt Ltd in Partnership with Wuhan Sinorock Technology Co. Ltd

- EIE Instruments Pvt Ltd, a leader in civil engineering testing instruments, has partnered with Wuhan Sinorock Technology Co. Ltd, a global expert in foundation pile testing.

- This collaboration brings advanced solutions for Pile Integrity Testing, Dynamic Analysis, Cross-Hole Sonic Logging, Static Load Testing, and Drilling Monitoring, combining EIE's trusted manufacturing and service with Sinorock's innovative technology.
- The partnership provides Indian infrastructure and geotechnical industries with reliable, efficient, and standards-compliant pile testing solutions, supporting engineers and contractors with accurate, safe, and streamlined foundation assessment.

EIE INSTRUMENTS PVT. LTD. | SINOROCK
(An ISO 9001 - 2015 Certified Company)

Construction Process Monitor Real-time and Accurate

RSM-HGT(D) ULTRASONIC DRILLING MONITOR

Hole/Trenching Quality Testing | Sediment Thickness Testing

• Dual-purpose Wet and Dry Hole Testing
• Intelligent Processing

Wide Applications | 3D Simulation | Intelligent Recognition | Advanced Precision Probes | Ultra-thin High-capacity Battery | Industrial Capacitive Screen

12.1-inch Industrial grade capacitive touch screen | 150m Maximum test depth | 20 cycles/sec Scanning speed | 3.0 kg Host weight

8h Long standby | -20~+55°C Fearless of the extreme environment | IP65 Dustproof and waterproof | Customization Support customized R&D

SINOROCK • MAKES TESTING AND MONITORING EASIER

Technical Specification

- Measuring Range : 600 ~ 8000mm; (hole/groove diameter)
- Max Measuring Depth : 150m (Can be customized)
- Max Depth Resolution : 5mm
- Record Mode : Color image, data file
- Data export method : USB

- Dimensions(Auto double winch) : 91 × 55 × 57 cm
- Weight of Auto double winch : 105kg

Corporate Office:

A-1301, BVR Ek, Opp. Hotel Inder Residency,
Near Gujarat College, Ellisbridge,
Ahmedabad-380 006.
Phone : (079) 6621 1234
Website : www.eieinstruments.com

Calibration Laboratory:

Survey No. 1098, Nr. Mahakali Temple,
Opp. Primary School, Village Kubadthal,
Tal-Daskroi, Ahmedabad-382 433.
Phone: (079)-3520 8300
E-mail : info@eieinstruments.com

GST TIN No. : 24AABCE4018L1ZU
I.T. PAN No. : AABCE 4018L
IEC No. : 0813026598 Dt. 04/03/2014
CIN No. : U29199GJ2004PTC045078
TAN No. : AHME00572F